



Genset  
Model:

## YXP180RSC

Enclosed set



Open set



Frequency

Phases

Power Factor

Prime Output

Standby Output

50Hz

3

0.8

180 kVA / 144 kW

198 kVA / 158 kW

### Ratings

- Prime output: This rating is applicable for supplying continuous electrical power at variable load. There is no limitation to the annual hours of operation and this model can supply 10% overload power for 1 hour in 12 hours.
- Standby output: This rating is applicable for supplying electrical power (at variable load) in the event of a utility power failure. No overload is permitted on these ratings.
- Standard reference conditions: 25°C, 100m A.S.L., 30% relative humidity

### Design features

- High quality assembly, providing stiffness and low vibration
- Power coated steel. Corrosion and scratch resistant.
- Compact and long service life
- Wiring and connectors with double protection.
- Protection guards in radiator and high voltage parts.
- Full 12 month YorPower warranty

### Design Standards

- CE marking
- ISO8528-1995
- GB/T2820-1997
- ISO 9001:2008 Registered Company

### Configuration

- 4-Stroke water-cooled diesel engine.
- Industrial silencer.
- Coolant recovery tank
- Single bearing, 4 pole brushless alternator.
- Anti vibration mountings
- Integral fuel tank with fully banded base protection.
- Fuel level sensor
- Auto start control system with electronic digital control module DSE7420
- Output circuit breaker.
- Emergency stop button
- High engine temperature and low oil pressure shutdown system.
- 24V starter battery with leads and switch

### Acoustic canopy features

- Water and dust proof design
- Door locks
- High quality sound absorbing and fire retardant inner material
- Lifting lugs
- Forklift holes in base

\*\* The images above are for illustration purposes only.

# GENERATOR WAREHOUSE

## Engine data





Engine brand	Perkins	Total coolant capacity	21 Litres
Engine model	1106A-70TAG3	Total lube oil capacity	16.5 Litres
Engine speed	1500 RPM	Cooling air flow	TBC
Number of cylinders	6	Exhaust gas flow	TBC
Aspiration	Turbo & Aftercooled	Exhaust gas temperature	TBC
Combustion system	Direct injection	Fuel cons. @ 110% standby load	TBC
Displacement	7.01 Litres	Fuel cons. @ 100% Prime load	TBC
Governor type	Mechanical	Fuel cons. @ 75% Prime load	TBC
Cooling system	Water Cooled	Fuel cons. @ 50% Prime load	TBC

## Alternator data

Alternator brand	Leroy Somer	Number of wires	12 re-connectable
Alternator model	LSA46.2M3	AVR model	R 250
Excitation	Self excited	Voltage regulation	± 0.5%
Insulation class	H	Total Harmonic distortion	< 2%
Drip proof protection	IP23	Telephone interference	TIF < 50%
Winding pitch	2/3 (wdg 6)	Flanges and shield	Cast Iron

## Enclosed set data

## Open set data



L x W x H (mm)	Weight	Fuel tank	Noise@7M
3518 x 1200 x 1842	2620 kg	420 Litres	70db

L x W x H (mm)	Weight	Fuel tank	Noise@7M
2751 x 836 x 1575	2142 kg	180 Litres	115db

\*\* Due to constant innovation, design and specifications are subject to change without notice.

### The Generator Warehouse Co Ltd

The Warehouse | Hurricane Close | Leeds | LS25 6PB

Web: [www.generatorwarehouse.co.uk](http://www.generatorwarehouse.co.uk)

Email: [info@generatorwarehouse.co.uk](mailto:info@generatorwarehouse.co.uk)

Tel: +44 (0)1977 800371

Registered: England and Wales No. 09054517

